



## Material

Polyamide nylon with glass fibre reinforced threaded nut. Zinc plated panhead torx drive screw, countersunk torx drive screw, screw eye or screw hook.

## General Information

- Heavy duty cavity fixed anchor
- Recommended for fixing heavy objects in plasterboards, chipboards, gypsum fibre boards or any cavity walls.
- Works with the same degree of safety whether used in insulataed cavities or standard cavities
- Clamping action imparts no load stresses on the substrate
- No special tools required.
- Recommended by leading plasterboard manufacturers.

## Installation

1. Drill 10 mm hole through the board. Hammer the Rosett flush with wall.
2. Place the screw in the fitting and tighten the screw.
3. On tightening, the anchor forms a knot on the back of the board (in the cavity).
4. Ensure screw is fully tightened, the anchor is now secure.



## Recommended max. load in plasterboards. Safety factor 3 applied.

Anchor type	Board thickness	Screw guage	Drill size	Direct tension	Vertical tension
Blue	9 - 12.5mm	5mm	10mm	45 kg	50 kg
Red	2 x 12.5mm			70 kg	85 kg

All information detailed in our data sheets is based on technical approvals, formulas and site and laboratory testing under optimum conditions and include a stated safety factor. As we have no direct or indirect control over where or how our products are applied or installed, we do not accept any liability either directly or indirectly arising from the use of our products, whether or not in accordance with any advice, specification or recommendation given by us and we recommend site testing of all products for suitability.